

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A45B 3/00	A1	(11) International Publication Number: WO 98/46101
		(43) International Publication Date: 22 October 1998 (22.10.98)
<p>(21) International Application Number: PCT/US98/07612</p> <p>(22) International Filing Date: 15 April 1998 (15.04.98)</p> <p>(30) Priority Data: 60/043,601 15 April 1997 (15.04.97) US</p> <p>(71) Applicant (for all designated States except US): INVACARE CORPORATION [US/US]; 899 Cleveland Street, Elyria, OH 44036 (US).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): OBITTS, SHANE [US/US]; 130 Illinois Circle, Elyria, OH 44035 (US).</p> <p>(74) Agents: FAGAN, Christopher, B. et al.; Fay, Sharpe, Beall, Fagan, Minnich & McKee, 7th floor, 1100 Superior Avenue, Cleveland, OH 44114-2518 (US).</p>		<p>(81) Designated States: CA, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>

(54) Title: UNIVERSAL PLATFORM SUPPORT FOR A WALKER

(57) Abstract

A universal platform support assembly (10) provides for vertical and horizontal adjustment to secure the assembly to a wide array of walker (W) styles and sizes. A forearm receiving member (20) can be pivoted for comfort of the user and a push handle (24) associated therewith may be selectively positioned fore and aft, as well as rotated, for additional fit and comfort. Enlarged knobs (32) that may be conveniently grasped and manipulated secure the various adjustable components together allowing assembly and adjustment to proceed without using tools.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

- 1 -

UNIVERSAL PLATFORM SUPPORT FOR A WALKER

BACKGROUND OF THE INVENTION

5 This invention relates to a patient aid and more particularly to a walker-type aid. More specifically, this invention relates to a platform support for use with a walker-type aid and will be described with particular reference thereto.

10 Walkers are well known in the prior art for assisting physically challenged individuals. Generally, walkers come in two sizes, i.e., an adult version and a juvenile version. Moreover, different style walkers are manufactured by a number of various companies. Walkers include four legs, two at each side. The front pair of legs are interconnected by a cross frame structure or the like. Likewise, the front and rear legs on each side are also
15 connected by a frame structure. In foldable or collapsible walkers, the side frame assemblies can be rotated inwardly for ease of storage. In other instances, however, the side frames remain in fixed relation relative to the cross frame structure, being maintained generally parallel to one
20 another.

The upper portion of each side frame is adapted to receive the user's hands. For example, hand grips are usually provided for comfort. Occasionally, however, a user is unable to grasp one of these hand regions and thus

- 2 -

requires a forearm support to balance that side of the user's body and grasp the walker. Accordingly, manufacturers have provided what are generally known as platform supports.

Platform supports are typically aftermarket assemblies that may be removably secured to a side frame of the walker. The platform support is usually secured to the hand grip region, as well as to a lower, transverse support bar that extends between the front and rear legs on the side frame of the walker. Tools such as screw drivers, wrenches, and the like are required for the conventional nut and bolt type fasteners used to secure the platform support in place on the walker. Moreover, known arrangements are not conducive to fitting both the juvenile and adult sizes of walkers. Further, platform supports usually are designed for use with one style of walker. Thus, patient aid or health care dealers must keep a variety of platform support styles in inventory to accommodate the different types and styles of walkers.

It is thus desirable to provide a platform support structure that includes a universal securing arrangement. That is, it will fit both juvenile and adult sizes, as well as fit a number of different manufacturers' styles of walkers.

SUMMARY OF THE INVENTION

The present invention provides a platform support assembly that is universal, easy to adjust and assemble and economical to manufacture.

- 3 -

According to the present invention, a platform support for a patient aid includes a forearm receiving member. The forearm receiving member is adapted for mounting to a side frame of the patient aid via a first securing assembly that is adjustable in a generally vertical direction.

According to another aspect of the invention, a second securing assembly is adapted for mounting the forearm receiving member to a side frame of the patient aid in a manner that is adjustable in a generally horizontal direction.

In accordance with the invention, the new platform support assembly includes an adjustable three-point attachment that is adjustable. The three-point attachment preferably includes a first area along the hand grip region, and second and third attachment points preferably located along the front and rear legs. Moreover, a main support tube can be easily raised and lowered within the three-point attachment to accommodate juvenile and adult-size walkers.

Additionally, the securing assemblies preferably use enlarged, easy to manipulate connectors or knobs for securing the assembly to a walker without using tools. This facilitates converting a standard walker to a platform type support.

A principal benefit of the invention is associated with the universal adaptation of the platform support assembly to different styles and sizes of walkers.

- 4 -

Another benefit of the invention resides in ease with which the platform support assembly can be secured to a walker.

Yet another benefit of the invention is found in the ability to alter the positions of components to accommodate the needs and comforts of an individual user.

Still other features and benefits will become apparent to those skilled in the art upon a reading and understanding of the following specification.

BRIEF DESCRIPTION OF THE DRAWINGS

Reference may be made to the following drawings which illustrate a preferred embodiment of the invention. The drawings do not, however, limit the scope of the invention. The drawings include:

FIGURE 1 is a perspective view of an upper portion of a conventional walker;

FIGURE 2 is an exploded perspective view of the present invention;

FIGURE 3 is a plan view of a portion of the forearm receiving member;

FIGURE 4 is an end view taken generally from the right-hand side of FIGURE 3; and

FIGURE 5 is a plan view of a portion of an alternative embodiment of the platform support assembly.

- 5 -

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings which illustrate the preferred embodiments of the invention only, FIGURE 1 illustrates a conventional walker W having a pair of side frames SF interconnected by a cross frame member CF. Each side frame includes a front leg FL and a rear leg RL that are connected at upper ends by a hand grip region HG. Additionally, the front and rear legs are connected by a support member SM that provides additional strength and rigidity to the walker. Lower ends (not shown) of the front and rear legs may include non-slip tips or the legs may include rollers, glide members, etc., depending on the particular needs of the user.

In the walker of FIGURE 1, manual actuators AC are provided on the front legs to independently fold the respective side frame into a folded, storage position adjacent the cross frame member CF from the open, operative position as illustrated. Suitable grips or cushion members GR are preferably provided in the hand grip region for grasping by a user.

FIGURE 2 illustrates a preferred embodiment of the invention. The platform support assembly is adapted for use on one or both of the side frames of a conventional walker to allow a patient to manipulate the walker without grasping the hand grip. Because the angular relationship and dimension between the front and rear legs may vary from one walker to another, and likewise the location of the support member SM may also vary, the platform support assembly of the present

- 6 -

invention is adaptable and adjustable to different sizes and styles. As shown, it includes a main support tube 10 that extends between first and second clamps 12, 14. The clamps are secured through the use of individual fasteners having enlarged handles or threaded knobs that can be easily manipulated by hand to secure the individual clamps, and thus the support tube, to an elongated clamp bracket to be described in greater detail below. At the upper end of the support tube is a two-piece arm support assembly or forearm receiving member 20. The forearm receiving member 20 is comprised of a pair of mirror-image members so that description of one is generally applicable to the other. The forearm receiving member has a triangular base portion 22, a central push-handle receiving portion 24, and an upper arm support portion 26 (see FIGURES 3 and 4). A series of fasteners 30 cooperate with threaded knobs 32 to secure the arm support assembly to an upper region of the support tube, and clamp the forearm receiving members together. An arcuate opening 34 allows the forearm receiving assembly to be selectively angularly positioned (as indicated by the directional arrows 36) on the top of the support tube for the comfort of the individual user. Thus, by loosening one of the fasteners via knob 32, the angular orientation of the forearm receiving assembly can be varied. Stated another way, it is not always desirable that the arm support be disposed orthogonal or perpendicular to the axis of the support tube. Accordingly, the arm support can be angularly

- 7 -

positioned within the range of movement provided by the arcuate opening 34 for a limited degree of tilt.

5 An arm tube 38 is received between the semicircular portions that define the push-handle receiving opening 24 in the arm support assembly. As will be recognized, the arm tube 38 may be adjustably positioned fore and aft (see arrows 40) within the push-handle receiving opening so that when an individuals' forearm is resting in the forearm receiving member 26, the upright portion of the handle grip can be
10 easily grasped by the user. Likewise, the arm tube can be rotated about the axis defined by the handle-receiving opening so that, if desired, further adjustment can be provided in this degree of freedom and as represented by arrows 42.

15 Received in the arcuate arm support is a cushion or foam member (if desired-not shown), a curvilinear upholstered arm portion 44, and a strap 46, such as a Velcro® strap, to secure the user's forearm in place. Elongated openings 48 are provided in the forearm receiving member to receive
20 opposite ends of the strap. The straps are then slid beneath the upholstered portion to conveniently secure the individual's forearm thereto.

A clamp bracket 50 (FIGURE 2) secures an upper end of the support tube 10 to the hand grip region of a
25 conventional walker. Particularly, an elongated opening 54 is provided on the bracket to receive a fastener associated with the upper clamp 12. Moreover, this fastener also

- 8 -

extends through a hinged clamp down member 56 adapted for receipt over the handle-receiving portion of a conventional walker. Thus, due to the hinged nature of the clamp, the bracket 50 is positioned along the outside of a side-framed walker, and the hinge portion extends over the handle into a position that is generally shown in FIGURE 2 whereby it receives the fastener associated with the upper clamp. This provides a first point of attachment of the platform support to a conventional walker.

In an alternative preferred embodiment of the clamp bracket designated 50' (FIGURE 5), the bracket is elongated and includes an opening 52 at a lower end adapted to receive the fastener for the lower clamp 14. For reasons which will become more apparent below, this arrangement does not have as much flexibility since the second and third attachment points are constrained to a connection region on the walker within range of the elongated opening 58.

Preferably secured to a lower region of the support tube 10 is a cross bracket or member 60 that has a pair of elongated grooves 62, 64 formed in opposite ends thereof. The cross bracket receives slide members 66, 68 which have openings therein adapted to receive fasteners and enlarged threaded knobs 70, 72, respectively. The outer ends of the slide members 66, 68 preferably have an arcuate configuration adapted for receipt about the legs (front and rear) of a side frame assembly of a walker. Elongated grooves 62, 64 allow these slide members to be advanced and retracted relative to

- 9 -

the cross bracket to accommodate different leg spacings on different manufacturer's walkers. Thus, the fastener and knob 72 and the arcuate outer ends of the slide members provide additional second and third points of attachment of the platform support to a walker.

By virtue of this assembly, a single-size platform support can accommodate both juvenile and adult-size walkers. The support tube 10 that carries the forearm receiving member can be raised and lowered relative to the clamps 12, 14 by simply loosening and tightening the knobs 18. Likewise, the forearm receiving assembly 20 can be angularly tilted by loosening and retightening knob 32, while additional knobs 32a, 32b allow the push-handle grip to be advanced forwardly and rearwardly in the handle-receiving opening, or rotated thereabout, for comfort of the user.

The entire assembly is easily secured to a side frame of a walker by folding the hinged portion of the bracket 50 about the hand grip of the walker frame. The fastener 18 associated with the upper clamp then completes the first point of attachment (and also provides for vertical adjustment, if necessary). Likewise, the slide members 66, 68 are conveniently secured about the front and rear legs of the walker on one side frame assembly, and the knobs 72 tightened to provide the second and third points of attachment (and also provide for horizontal adjustment, if necessary). Since the position of the bracket 50 and the slide members 66, 68 can be selectively altered, the platform

- 10 -

support is adaptable to a wide variety of walker styles and sizes.

This arrangement allows the universal attachment of a platform support to a side frame assembly of a walker. It will also be understood that the same platform support can alternatively be used on either the left-hand or right-hand side frame. If necessary, platform attachments can be provided on each side frame assembly of the walker. Moreover, this structural arrangement easily accommodates both juvenile and adult versions of walkers and can be easily and conveniently fitted to a wide variety of manufacturers' structures. The enlarged threaded knobs are easily manipulated for simple adjustment, if necessary, without using any tools or special fasteners. Moreover, the three points of attachment to the conventional walker eliminates any concern with the location of the support member that interconnects the front and rear legs of a walker side frame. As may be expected, the location, size, and configuration of the support member may vary from one manufacturer to another. Thus, using the hand grip region and the front and rear legs as the preferred three points of attachment of the platform support eliminates any concerns with the various support members SM that may be used by different manufacturers.

The invention has been described with reference to the preferred embodiments. Obviously, modifications and alterations will occur to others upon a reading and understanding of this specification. It is intended to include all such modifications and alterations insofar as

- 11 -

they come within the scope of the appended claims or the equivalents thereof.

- 12 -

Having thus described the invention, it is now claimed:

5 1. A universal platform support for a walker-type patient aid that includes a front leg and a rear leg on each side thereof comprising:

 a forearm receiving member contoured to receive a forearm of an associated user;

10 an adjustable first securing assembly operatively associated with the forearm receiving member having an attachment member that permits adjustment of the forearm receiving member in a generally vertical direction; and

15 an adjustable second securing assembly operatively associated with the forearm receiving member and having an attachment member that is adjustable in a generally horizontal direction.

20 2. The platform support of claim 1 further comprising a support member operatively connected to and supporting the forearm receiving member.

25 3. The platform support of claim 1 wherein the first securing assembly includes a clamp bracket adapted for receipt about a hand receiving grip of a walker-type aid.

 4. The platform support of claim 3 wherein the clamp bracket includes an elongated slot permitting the clamp

- 13 -

bracket to be adjusted vertically relative to the support member.

5. The platform support of claim 4 wherein the first
5 securing assembly includes an enlarged hand-manipulable knob that may be rotated to tighten and loosen the clamp bracket for adjustment without using tools.

10 6. The platform support of claim 3 wherein the clamp bracket is a split member having first and second portions hinged along a common edge whereby the first and second portions may be selectively opened and closed to adapt the clamp bracket for receipt about an associated hand receiving grip on a walker-type aid.

15 7. The platform support of claim 1 wherein the second securing assembly includes first and second contoured surfaces adapted for receipt about legs of a walker-type aid.

20 8. The platform support of claim 7 wherein the contoured surfaces include first and second arcuate ends adapted for receipt about legs of a walker-type aid.

25 9. The platform support of claim 7 wherein each of the first and second contoured surfaces is independently adjustable relative to the support member in a generally horizontal direction.

- 14 -

10. The platform support of claim 7 including an enlarged hand-manipulable knob that may be rotated to tighten and loosen the second securing assembly for generally vertical adjustment without using tools.

5

11. The platform support of claim 7 including first and second enlarged hand-manipulable knobs associated with the first and second contoured surfaces, respectively, that may be selectively tightened and loosened for adjusting the horizontal position of the contoured surfaces without using tools.

10

12. The platform support of claim 1 further comprising a push handle disposed adjacent the forearm receiving member adapted for gripping by an associated user.

15

13. The platform support of claim 12 further comprising a push handle mounting assembly that allows selective adjustment of the push handle fore and aft relative to the forearm receiving member.

20

14. The platform support of claim 12 further comprising a push handle mounting assembly that allows selective rotational adjustment of the push handle relative to the forearm receiving member.

25

15. The platform support of claim 1 further comprising a forearm mounting member interconnecting the forearm

- 15 -

receiving member to the support member, the forearm mounting member including an angle adjusting portion for selectively altering the angular orientation of the forearm receiving member.

5


16. The platform support of claim 15 wherein the forearm receiving member includes first and second portions received on opposite sides of the support member and cooperatively defining an arcuate recess adapted to receive a user's forearm therein.

10


17. The platform support of claim 15 further including an enlarged knob for securing the forearm mounting member to the support member without the use of tools.

15




18. The platform support of claim 15 further including an enlarged knob associated with the angle adjusting portion for altering the angle of the forearm receiving member without the use of tools.

*Fig. 1*

2/3



SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/07612

A. CLASSIFICATION F SUBJECT MATTER IPC(6) :A45B 3/00 US CL :Please See Extra Sheet According to International Patent Classification (IPC) or to both national classification and IPC																								
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 135/66, 67, 71, 72, 76; 482/66, 68; 297/5-7; 280/87.021, 87.041, 87.051 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched none Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) none																								
C. DOCUMENTS CONSIDERED TO BE RELEVANT																								
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																						
X	US 4,248,256 A (THOMAS) 03 FEBRUARY 1981 (03/02/81). SEE ENTIRE DOCUMENT.	1-3, 6-8, 10-18																						
A	US 4,748,994 A (SCHULTZ ET AL.) 07 JUNE 1988 (07/06/88). SEE ENTIRE DOCUMENT.	1-18																						
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.																								
<table border="0"><tr><td>* Special categories of cited documents:</td><td>* T</td><td>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td></tr><tr><td>* A</td><td>document defining the general state of the art which is not considered to be of particular relevance</td><td></td></tr><tr><td>* E</td><td>earlier document published on or after the international filing date</td><td>* X</td><td>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td></tr><tr><td>* L</td><td>document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td><td>* Y</td><td>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td></tr><tr><td>* U</td><td>document referring to an oral disclosure, use, exhibition or other means</td><td>* A</td><td>document member of the same patent family</td></tr><tr><td>* P</td><td>document published prior to the international filing date but later than the priority date claimed</td><td></td><td></td></tr></table>			* Special categories of cited documents:	* T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	* A	document defining the general state of the art which is not considered to be of particular relevance		* E	earlier document published on or after the international filing date	* X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	* L	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	* U	document referring to an oral disclosure, use, exhibition or other means	* A	document member of the same patent family	* P	document published prior to the international filing date but later than the priority date claimed		
* Special categories of cited documents:	* T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention																						
* A	document defining the general state of the art which is not considered to be of particular relevance																							
* E	earlier document published on or after the international filing date	* X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone																					
* L	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art																					
* U	document referring to an oral disclosure, use, exhibition or other means	* A	document member of the same patent family																					
* P	document published prior to the international filing date but later than the priority date claimed																							
Date of the actual completion of the international search 26 MAY 1998		Date of mailing of the international search report 18 JUN 1998																						
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer <i>Diana Gordon</i> LANNA MAI Telephone No. (703) 308-2168																						

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/07612

A. CLASSIFICATION OF SUBJECT MATTER:
US CL :

135/66, 67, 71, 72, 76; 482/66, 68; 297/5-7; 280/87.021, 87.041, 87.051